

1254 Chestnut Street Newton, MA 02464-1418 Tel: (617) 965-5511 Fax: (617) 965-5818

MATERIAL SAFETY DATA SHEET

PAGE 1 03 March 2005

SECTION 1. CHEMICAL IDENTIFICATION -----

| CHEMICAL NAME: TRADE NAME: PRODUCT #: | Organic Polymer Solution 495 PMMA Series Resists in Anisole Positive Radiation Sensitive Resists See Table 1 – Section 9 | |
|---|---|--|
| SECTION 2. COMPOSIT | ION | |
| HAZARDOUS INGREDIENTS: OTHER INGREDIENTS: | Anisole (CAS: 100-66-3); 84-99% (See Table 1 – Section 9) Poly(methylmethacrylate) (CAS: 9011-14-7) | |
| | | |
| SECTION 3. HAZARD D | ATA | |
| INFLAMMABILITY: SKIN CONTACT: EYE CONTACT: INHALATION: | Flammable liquid. May cause skin irritation. Vapor or mist is irritating to the eyes. Vapor or mist is irritating to mucous membranes and upper | |
| MUTAGENICITY: CARCINOGENICITY: TARGET ORGANS: | respiratory tract. Not known to be mutagenic. Not known to be carcinogenic. Eyes, Skin, Respiratory System, and Nervous System. | |
| SECTION 4. FIRST AID | MEASURES | |
| INHALATION: INGESTION: SKIN CONTACT: | Move the affected person away from the contaminated area and into the fresh air. If necessary seek medical advice. Rinse mouth out with water. Consult a doctor if necessary. | |
| EYE CONTACT: | Rinse with plenty of water. Rinse with water while keeping the eyes wide open. | |
| SECTION 5. FIRE FIGHTING MEASURES | | |
| EXTINGUISHING MEDIA SPECIAL FIRE FIGHTING PRECAUTIONS: | | |
| UNUSUAL FIRE OR EXPLOSION HAZARDS: | and eyes. Heat will build pressure and may rupture closed containers. Keep containers cool with water spray. | |

| CHEMICAL NAME: | Organic Polymer Solution |
|----------------|--------------------------------------|
| TRADE NAME: | 495 PMMA Series Resists in Anisole |
| | Positive Radiation Sensitive Resists |
| PRODUCT #: | See Table 1 – Section 9 |
| | |

SECTION 6. ACCIDENTAL RELEASE PROCEDURES ------

EVACUATION DDOCEDUDES & SAFETV.

| PROCEDURES & SAFETY: | Wear appropriate protective gear for the situation. See Personal Protection information in Section 8. Eliminate all sources of ignition. Do not breathe vapors or dust. |
|---------------------------------------|---|
| CLEANUP & DISPOSAL OF SPILL: | Absorb with an inert absorbent. Sweep up and place in an appropriate closed container. Use clean, non-sparking tools to collect absorbed material. |
| ENVIRONMENTAL & REGULATORY REPORTING: | Do not flush to drain. If required proper authorities should be |

SECTION 7. STORAGE AND HANDLING PRECAUTIONS------

notified.

| Store in tightly closed container in a cool, dry, well-ventilated |
|---|
| environment away from ignition source. |
| Use only under yellow light. |
| Keep away from heat, sparks, and flames. |
| Use only with mechanical exhaust. |
| Do not contact with skin, eyes, and clothing. |
| Avoid prolonged or repeated contact with skin. |
| Do not breathe vapors or mist. |
| Wash with soap and water after handling. |
| Have safety shower and eye wash available. |
| Store and transfer under a blanket of dry inert gas. |
| |

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION------

RESPIRATORY **PROTECTION:** Under normal conditions, use of air-purifying (half-mask/full-face) respirator with cartridges/canisters approved for use against organic **VENTILATION:** SKIN PROTECTION:

vapors, dust, mists and fumes is recommended. General area dilution/exhaust ventilation. PVC protective gloves are highly recommended. **EYE PROTECTION:** Safety goggles are highly recommended.

| CHEMICAL NAME: | Organic Polymer Solution |
|----------------|--------------------------------------|
| TRADE NAME: | 495 PMMA Series Resists in Anisole |
| | Positive Radiation Sensitive Resists |
| PRODUCT #: | See Table 1 – Section 9 |
| | |

SECTION 9. PHYSICAL AND CHEMICAL DATA-----

| Clear to straw colored liquid |
|-------------------------------|
| Strong |
| 154 °Č (309 °F) |
| See Table 1 below |
| 13 mm @ 42 °C (108 °F) |
| 3.7 (air=1) |
| Slightly soluble. |
| See Table 1 below |
| 0.1 (BuAc=1) |
| 44 °C (111 °F) CC |
| 475 °C (887 °F) |
| unk. Lower |
| unk. Upper |
| |

Table 1

| Name | Product # | Specific Gravity | Volatiles (% by wt.) | VOC (g/L) |
|----------|-----------|------------------|----------------------|-----------|
| 495A1 | M130001 | 0.995 | 99 | 985 |
| 495A2 | M130002 | 0.997 | 98 | 975 |
| 495A3 | M130003 | 0.999 | 97 | 970 |
| 495A4 | M130004 | 1.001 | 96 | 960 |
| 495A4.5 | M130504 | 1.002 | 95.5 | 957 |
| 495A5 | M130005 | 1.003 | 95 | 955 |
| 495A5.5 | M130505 | 1.004 | 94.5 | 950 |
| 495A6 | M130006 | 1.005 | 94 | 945 |
| 495A7 | M130007 | 1.007 | 93 | 935 |
| 495A7.5 | M130507 | 1.008 | 92.5 | 930 |
| 495A8 | M130008 | 1.009 | 92 | 930 |
| 495A8.5 | M130508 | 1.010 | 91.5 | 925 |
| 495A9 | M130009 | 1.011 | 91 | 920 |
| 495A10 | M130010 | 1.013 | 90 | 910 |
| 495A11 | M130011 | 1.014 | 89 | 900 |
| 495A15 | M130015 | 1.018 | 85 | 865 |
| 495A15.5 | M130515 | 1.019 | 84.5 | 860 |

SECTION 10. REACTIVITY DATA ------

STABILITY: INCOMPATIBILITY: HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Stable Strong Oxidizing Agents, Strong Acids, Strong Bases Carbon Monoxide, Carbon Dioxide, Phenol

| CHEMICAL NAME: | Organic Polymer Solution |
|----------------|---|
| TRADE NAME: | 495 PMMA Series Resists in Anisole |
| PRODUCT #: | Positive Radiation Sensitive Resists See Table 1 – Section 9 |

SECTION 11. TOXICITY HAZARDS------

ACUTE TOXICITY:

As Anisole:

| ORAL: | LD50 (rat): | 3700 mg/kg |
|-------|-------------|-------------|
| SKIN: | LD50 (rat): | >5000 mg/kg |

LOCAL EFFECTS: Slightly irritating to the skin. Not irritating to rabbits on ocular application. No sensitizing reaction was observed for guinea pigs.

SECTION 12. ECOLOGICAL DATA-----

| BIODEGRADABILITY: | Readily biodegradable. |
|-------------------------|---------------------------------|
| BIOACCUMULATION: | Not potentially bioaccumulable. |
| ECOTOXICITY: | EC50 (Daphnia/24 hr): 40 mg/l |

SECTION 13. DISPOSAL CONSIDERATIONS------

Comply with applicable local, state or international regulations regarding the proper disposal of this material and/or containers.

SECTION 14. TRANSPORTATION INFORMATION------

HAZARD CLASSIFICATION: SHIPPING NAME: UN NUMBER: PACKING GROUP: Flammable Liquid Resin Solution UN 1866 III

SECTION 15. REGULATORY INFORMATION------

EUROPEAN INFORMATION

EINECS LISTED EC Nos: Anisole 202-876-1 RISK & SAFETY PHRASES R10 Flammable S16 Keep away from sources of ignition. No smoking. S24 Avoid contact with skin. INDICATIONS OF DANGER None

| CHEMICAL NAME: | Organic Polymer Solution |
|----------------|--------------------------------------|
| TRADE NAME: | 495 PMMA Series Resists in Anisole |
| | Positive Radiation Sensitive Resists |
| PRODUCT #: | See Table 1 – Section 9 |
| | |

US AND INTERNATIONAL INFORMATION

| HAZARDOUS LISTINGS: | All ingredients appear on the TSCA Inventory of Chemical Substances, EINECS, Canadian DSL and the |
|---------------------|--|
| SARA Title III: | Japan ENCS Listing. This product IS NOT subject to SARA Title III, Section 313 Reporting Requirements. |

Calif. SCAQMD Rule 443.1 VOC's: See Table 1 – Section 9

SECTION 16. ADDITIONAL PRECAUTIONS AND COMMENTS------

National Fire Protection Association Hazard Ratings – NFPA:

- 1 Health Hazard Rating
- 2 Flammability Rating
- 0 Reactivity Rating

To the best of our knowledge, the above information is believed to be accurate but does not claim to be all-inclusive and is intended to be used only as a guide. The supplier makes no warranty of any kind, expressed or implied, concerning the use of this product and shall not be held liable for any damage resulting from handling or from contact with the above product. User assumes all risks incident to its use.

MSDS Revision Information:

A) Removed "NANO" name from trade name.

B) General update of MSDS. Added European Risk and Safety phrases to Section 15.